

# Low and Medium Temperature Compressors - A2L

Model	Application	Motor	HP	Displ. [cc]	Evap. Range [°C]	R455A (EN12900, Tc +45°C)				R454C (EN12900, Tc +45°C)				Diameter	
						CAP [W]	COP [W/W]	CAP [W]	COP [W/W]	CAP [W]	COP [W/W]	CAP [W]	COP [W/W]	Suction	Liquid
						-10°C	-10°C	-5°C	-5°C	-10°C	-10°C	-5°C	-5°C		
NEU6212GL	MBP	CSIR	1/2	8,77	-20° to 10°	680	1,74	843	2,00	611	1,65	761	1,89	5/16	15/64
NEU6215GL	MBP	CSR	3/4	12,11	-20° to 10°	969	1,87	1199	2,14	871	1,77	1081	2,02	5/16	15/64
NT6222GL	MBP	CSR	1	17,39	-20° to 10°	1199	1,74	1529	2,07	1112	1,70	1412	2,01	3/8	1/4
NT6224GL	MBP	CSR	1	20,44	-20° to 10°	1342	1,78	1731	2,11	1244	1,73	1598	2,05	3/8	1/4
NT6226GL	MBP	CSR	1+	22,37	-20° to 10°	1506	1,77	1922	2,07	1396	1,71	1774	2,01	3/8	1/4
NJ9232GM	MBP	3phase	1 1/4	26,11	-20° to 10°	1720	1,73	2175	1,98	1585	1,66	2001	1,90	1/2	5/16
NJ9232GL	MBP	CSR	1 1/4	26,11	-20° to 10°	1833	1,76	2331	2,06	1690	1,69	2145	1,99	1/2	5/16
NTU6238GLV	MBP	CSR	1 1/2	26,21	-20° to 10°	1966	1,99	2463	2,32	1840	1,96	2300	2,28	1/2	3/8
NJ9238GM	MBP	3phase	1 1/2	32,67	-20° to 10°	2233	1,75	2797	1,97	2065	1,72	2585	1,94	1/2	5/16
NJX6250GM	MBP	3phase	2	37,88	-20° to 10°	2893	1,92	3583	2,16	2729	1,93	3386	2,18	1/2	5/16

Model	Application	Motor	HP	Displ. [cc]	Evap. Range [°C]	R455A (EN12900, Tc +45°C)				R454C (EN12900, Tc +45°C)				Diameter	
						CAP [W]	COP [W/W]	CAP [W]	COP [W/W]	CAP [W]	COP [W/W]	CAP [W]	COP [W/W]	Suction	Liquid
						-25°C	-25°C	-30°C	-30°C	-25°C	-25°C	-30°C	-30°C		
NT2180GL	LBP	CSR	1	20,44	-40° to -10°	686	1,24	503	1,05	637	1,23	469	1,03	3/8	1/4
NT2192GL	LBP	CSR	1+	22,37	-40° to -10°	716	1,26	521	1,07	664	1,25	486	1,05	3/8	1/4
NT2212GL	LBP	CSR	1 1/2	27,8	-40° to -10°	941	1,26	701	1,09	873	1,25	654	1,07	3/8	1/4
NJX2219GS	LBP	3phase	2 1/4	37,88	-40° to -10°	1482	1,36	1117	1,18	1413	1,38	1075	1,20	1/2	5/16